

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## **IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.

**Claim Restriction Under 35 USC §121**

Claims 1-33 were originally pending. Claims 1-33 stand restricted under 35 U.S.C. §121 as containing three patentably distinct inventions. In particular, the Office action ("Action") asserts that the following claim groupings represent three distinct or independent inventions as follows:

- Group I, Claims 1-17 drawn to a remote controller, classified in Class 700, subclass 65.
- Group II, Claims 18-22 drawn to a clock radio, classified in Class 455, subclass 231.
- Group III, Claims 23-33 drawn to a computer readable medium and a method to detect a device with user interface which is located within a proximity of the computer, classified in Class 700, subclass 17.

In view of this restriction requirement, claims 18-33 are withdrawn from consideration under 35 USC §1.142(b), as being drawn to non-elected subject matter. Claims 1-17 are elected for continued examination. Accordingly, claims 1-17 remain pending.

1 **In the Claims**

2 1. (original) A remote controlled system comprising:  
3 a remote controller; and  
4 a general-purpose computer coupled to communicate with the remote  
5 controller and a controlled device to facilitate remote control of the controlled  
6 device by the remote controller.

7  
8 2. (original) A remote controlled system of claim 1, wherein the remote  
9 controller has a display and one or more input mechanisms that enable user input.

10  
11 3. (original) A remote controlled system of claim 1, wherein the remote  
12 controller is embodied as a cellular phone.

13  
14 4. (original) A remote controlled system of claim 1, wherein the  
15 controlled device is embodied as a home device selected from a group of home  
16 devices comprising a television, a stereo, a radio, a VCR, a set top box, lighting  
17 controller, and alarm controller.

18  
19 5. (original) A remote controlled system of claim 1, wherein the  
20 general-purpose computer is embodied as a desktop computer.

21  
22 6. (original) A remote controlled system of claim 1, wherein the  
23 general-purpose computer runs an open platform operating system.  
24  
25

1       7. A remote controlled system of claim 1, wherein the general-purpose  
2 computer is configured to expose a universal plug and play (UPnP) application  
3 program interface (API) through which the remote controller and the controlled  
4 device may make calls to the general-purpose computer.

5  
6       8. (original) A remote controlled system of claim 1, wherein the  
7 general-purpose computer is configured to communicate with the remote  
8 controller and the controlled device using a wireless communication protocol.

9  
10       9. (original) A remote controlled system of claim 1, further comprising  
11 an application program stored and executed on the general-purpose computer, the  
12 application program directing the computer to provide UI information to the  
13 remote controller that may be used by a user to enter control data for controlling  
14 the controlled device and to translate the control data received from the remote  
15 controller into commands that are sent to the second device to effectuate an action  
16 intended by the user.

17  
18       10. (original) A remote controlled system of claim 1, further comprising  
19 multiple remote controllers and multiple controlled devices, the general-purpose  
20 computer is coupled to communicate with the multiple remote controllers and the  
21 multiple controlled devices to facilitate remote control of any one of the controlled  
22 devices by any one of the remote controllers.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

11. (original) A remote controlled system comprising:

a first device having a user interface (UI); and

a facilitator communicatively coupled to the first and a second device to facilitate remote control of the second device by the first device, the facilitator providing UI information to the first device that may be used by a user to enter control data for controlling the second device to perform an action, the facilitator translating the control data received from the first device into commands that are sent to the second device to effectuate the action intended by the user.

12. (original) A remote controlled system of claim 11, wherein the facilitator comprises a general-purpose computer.

13. (original) A remote controlled system of claim 11, wherein the facilitator comprises a general-purpose computer that runs an open platform operating system.

14. (original) A remote controlled system of claim 11, wherein the facilitator is configured to expose a universal plug and play (UPnP) application program interface (API) through which the first and second devices may make calls to the facilitator.

1       15. (original) A remote controlled system of claim 11, wherein the  
2 facilitator is configured to communicate with the first and second devices using a  
3 wireless communication protocol.  
4

5       16. (original) A remote controlled system of claim 11, wherein the UI of  
6 the first device comprises one or more input components to permit user entry of  
7 the control data, the UI information being associated with the input components so  
8 that selection of a particular input component by the user results in generation of  
9 particular control data.  
10

11       17. (original) A remote controlled system of claim 11, wherein the UI of  
12 the first device includes a display and the UI information includes text strings for  
13 display on the UI display.  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

1  
2       18.   (withdrawn) A clock radio comprising:  
3       a clock;  
4       a user interface (UI) to enable user input;  
5       one or more speakers; and  
6       a general-purpose computer, remote from but communicatively coupled to  
7 the UI and speakers, to facilitate remote control of the speakers by the UI.

8  
9       19.   (withdrawn) A clock radio of claim 18, wherein the clock, the UI,  
10 and the speakers are integrated in a common housing.

11  
12       20.   (withdrawn) A clock radio of claim 18, wherein the general-purpose  
13 computer runs an open platform operating system.

14  
15       21.   (withdrawn) A clock radio of claim 18, wherein the general-purpose  
16 computer is configured to expose a universal plug and play (UPnP) application  
17 program interface (API) through which the UI and the speakers may make calls to  
18 the general-purpose computer.

19  
20       22.   (withdrawn) A clock radio of claim 18, wherein the general-purpose  
21 computer is configured to communicate with the UI and the speakers using a  
22 wireless communication protocol.  
23  
24  
25

1  
2       23.   (withdrawn) A computer, comprising:  
3       one or more processors;  
4       computer-readable media including computer-executable instructions that,  
5   when executed by the one or more processors, cause the computer to:  
6       send information to a first device to configure a display means in the first  
7   device to display information related to the control of a second device;  
8       receive from the first device control data for controlling the second device;  
9       convert the received control data into control commands for the second  
10   device; and  
11       send the control commands to the second device.

12  
13       24.   (withdrawn) A computer as defined in claim 23, wherein the first  
14   device and the second device are physically connected.

15  
16       25.   (withdrawn) A computer as defined in claim 23, wherein the  
17   computer-executable instructions further cause the computer to expose a set of  
18   universal plug and play (IPnP) application program interfaces (APIs) through  
19   which information may be communicated to the first device.

20  
21       26.   (withdrawn) A computer as defined in claim 23, wherein the  
22   computer-executable instructions further cause the computer to receive and store a  
23   schema of the first device.



1       27. (withdrawn) A computer as defined in claim 23, wherein the  
2 computer-executable instructions further cause the computer to receive and store a  
3 schema of the first device, the schema including a description of the first device.  
4

5       28. (withdrawn) A system comprising:  
6 a remote controller having a user interface (UI); and  
7 a general-purpose computer in communication with the remote controller;  
8 and  
9 computer-readable media including computer-executable instructions that,  
10 when executed by the general-purpose computer, cause the general-purpose  
11 computer to:  
12 receive from the remote controller information defining operational  
13 parameters of the UI;  
14 send information to the remote controller to configure the UI to display  
15 information related to the control of a controlled device and to receive user input  
16 for the control of the controlled device;  
17 receive from the remote controller data for controlling the controlled  
18 device; and  
19 send control commands to the controlled device, the control commands  
20 being based on the received control data.  
21

22       29. (withdrawn) A system as defined in claim 28, wherein the controlled  
23 device comprises a wireless device.  
24  
25

1       30. (withdrawn) A system as defined in claim 28, wherein the UI  
2 comprises a display screen.

3  
4       31. (withdrawn) A system as defined in claim 28, wherein the UI  
5 comprises a display screen and user input means.

6  
7       32. A system as defined in claim 28, wherein the information defining  
8 operational parameters of the UI comprise a schema.

9  
10       33. (withdrawn) A system comprising:  
11 means for sending information to configure a user interface (UI) in a first  
12 wireless device;

13       means for receiving from the first wireless device control data for  
14 controlling a second wireless device, the control data being based on user  
15 interaction with the UI of the first wireless device; and

16       means for sending control commands to the second wireless device, the  
17 control commands being based on the received control data.

18  
19  
20       Respectfully Submitted,

21  
22       Dated: 6-22-2004

By: 

Steven J. Spellman  
Reg. No. 45,124  
(509) 324-9256